



ACRY-Glue TDS

1.0 General Description

ACRY-Glue is a ready to use 100% acrylic latex glue specifically designed for modern fabric and fiberglass crack repair systems. ACRY-Glue maintains crack system flexibility while reducing the likelihood of cracking.

ACRY-Glue does not contain the same latex used for filling cracks, often named Sport Patch, Deep Patch or other "Patch" products. "Patch" latexes are too hard and lack the adhesion necessary for long lasting crack system repairs. ACRY-Glue does not contain any asbestos, lead or mercury.

ACRY-Glue can be applied with varying sizes of nap rollers, squeegees and brushes.

2.0 Safety Guidelines

Avoid contact with eyes, skin and clothing. Refer to MSDS for additional information.

3.0 Storage and Handling

Protect from freezing. Store between 4°C (40°F) and 32°C (90°F).

Packaging: 55 gallon drum (550 lbs.), 30 gallon drum (300 lbs.), 5 gallon pail (50 lbs.). Drums are heavy. Use caution when moving.

4.0 Coverage

Coverage varies upon crack system and width of cracks, 15 – 25 linear feet per gallon.

5.0 Physical Properties

Weight per gallon	9.4 lbs
Solids Content by weight	37%
Binder Content by weight	48%

A product of Stegas, Inc.

www.Tennispaint.com

2988 Angelletta Dr. Austell, GA 30106