



# WHITE LINE PAINT TDS

## 1.0 General Description

ACRYTECH White Line Paint is a 100% Acrylic Latex Emulsion textured line marking paint. It is uniquely formulated to leave crisp, clean lines in one coat. For competition courts and even crisper lines, prime with ACRYTECH Line Primer. ACRYTECH White Line Paint is designed for use on asphalt or concrete based tennis courts, basketball courts, running tracks, volleyball courts, and other recreational surfaces. It is highly resistant to wear and ultra-violet degradation and does not contain any asbestos, lead or mercury.

## 2.0 Safety Guidelines

Avoid contact with eyes, skin and clothing. Refer to Safety Data Sheet for additional information.

## 3.0 Storage and Handling

Protect from freezing. White Line Paint should be stored between 4°C (40°F) and 32°C (90°F).  
Packaging: 1 gallon squeeze bottles (11 lbs).

## 4.0 Coverage

1 gallon covers one tennis court (480 linear feet at 2" wide).

## 5.0 Application

Apply only after ACRYTECH Colorguard is thoroughly dry, up to 24 hours after final coat. Apply 1 (2<sup>nd</sup> optional) coat with soft bristle brush or high quality roller. Apply up to 20 feet at a time if ambient air temperature exceeds 30°C (86°F). Apply up to 40 feet at a time if ambient air temperature is under 30°C (86°F).

## 6.0 Limitations

DO NOT APPLY WHEN:

1. Rain is in the near forecast.
2. Surface temperatures exceed 54°C (130°F).
3. Ambient air temperatures are below 10°C (50°F).

A product of Stegas, Inc.

[www.Tennispaint.com](http://www.Tennispaint.com)

2988 Angellet Dr. Austell, GA 30106