



## CRACK FILLER TDS

ACRYTECH Crack Filler is a 100% acrylic latex based, tinted, high solids filler. Available in all standard colors, Crack Filler is intended to temporarily repair cracks up to ½” during playing season until a complete resurfacing can be completed.

Crack Filler has a working time of approximately 5-10 minutes.

### **1.0 SCOPE**

For use on all foot traffic based asphalt and concrete surface cracks under ½”.

### **2.0 PREPARATION**

Clean crack of debris, loose dirt, oil or grease using pressurized air or a pressure washer. Crack must be dry prior to application.

### **3.0 APPLICATION**

- 3.1** Hand fill cracks with a straight edge, trowel or spatula
- 3.2** Wipe crack filler from edges with a damp cloth to remove build up
- 3.3** Allow 24 hours for curing. Very deep patches may require longer curing time.
- 3.4** Sand or scrape rough edges as needed.

### **4.0 COVERAGE**

Varies depending on the dimensions of the crack. 1 gallon fills crack 20’ long x ½” wide x 2” deep.

### **5.0 LIMITATIONS**

Deep Crack Filler applications in extremely hot weather can experience a false curing. The surface will skim over and the repair will appear to be hard in a matter of hours. Caution should be taken to ensure that the repair has cured throughout, estimated at 24 hours. Do not apply when temperatures are under 50°F or rain is expected within 24 hours.

### **6.0 PHYSICAL PROPERTIES**

Colors	10 standard
Weight per gallon	15 lbs
Solids Content, %	85

A product of Stegas, Inc.

[www.tennispaint.com](http://www.tennispaint.com) | 888-294-0428

2660 Easterly Place | Decatur, GA 30035