



LINE PRIMER TDS

1.0 General Description

ACRYTECH Line Primer is a 100% Acrylic Latex Emulsion clear drying primer applied prior to ACRYTECH White Line Paint. Line Primer is not necessary for most line markings but is designed to create an even cleaner and crisper line demanded on competition surfaces. ACRYTECH Line Primer does not contain any asbestos, lead or mercury.

2.0 Safety Guidelines

Avoid contact with eyes, skin and clothing. Refer to MSDS for additional information.

3.0 Storage and Handling

Protect from freezing. Line Primer should be stored between 4°C (40°F) and 32°C (90°F).
Packaging: 1 gallon squeeze bottles (9 lbs).

4.0 Coverage

1 gallon covers up to 1.5 tennis court lines (600-750 linear feet at 2" wide)

5.0 Application

Apply only after ACRYTECH Colorguard is thoroughly dry, up to 24 hours after final coat. Apply 1 coat with soft bristle brush or hig- quality roller. Line primer is ready to paint when dry to the touch, usually 1-2 hours.

8.0 Limitations

DO NOT APPLY WHEN:

1. Rain is in the near forecast
2. Surface temperatures exceed 54°C (130°F).
3. Do not apply when ambient air temperatures are below 10°C (50°F)