



WHITE LINE PAINT TDS

1.0 General Description

ACRYTECH White Line Paint is a 100% Acrylic Latex Emulsion textured line marking paint. It is uniquely formulated to leave crisp, clean lines without needing a line primer/sealer and only in one coat. It is designed for use on asphalt or concrete based tennis courts, basketball courts, running tracks, volleyball courts, and other recreational surfaces. ACRYTECH White Line Paint is highly resistant to wear and ultra-violet degradation and does not contain any asbestos, lead or mercury.

2.0 Safety Guidelines

Avoid contact with eyes, skin and clothing. Refer to MSDS for additional information.

3.0 Storage and Handling

Protect from freezing. White Line Paint should be stored between 4°C (40°F) and 32°C (90°F).

Packaging: 1 gallon squeeze bottles (11 lbs).

4.0 Coverage

1 gallon covers one tennis court (480 linear feet at 2" wide)

5.0 Application

Apply only after ACRYTECH Colorguard is thoroughly dry, up to 24 hours after final coat. Apply 1 (2nd optional) coat with soft bristle brush or high-quality roller. Apply up to 20 feet at a time if ambient air temperature exceeds 30°C (86°F). Apply up to 40 feet at a time if ambient air temperature is under 30°C (86°F).

8.0 Limitations

DO NOT APPLY WHEN:

1. Rain is in the near forecast
2. Surface temperatures exceed 54°C (130°F).
3. Do not apply when ambient air temperatures are below 10°C (50°F)

A product of Stegas, Inc.

www.Tennispaint.com

2988 Angellette Dr. Austell, GA 30106