

AcryTrack Tack Coat

Latex primer for tack coating used in the construction of rubberized running tracks

For sports surface applications, AcryTrack Tack Coat serves as a tack coat primer for use in running track installation. It provides adhesion to asphalt for the first layer of rubber particles and gives the first layer of rubber a strong adhesion bond.



Physical Properties

Chemistry Type	Carboxylated styrene butadiene [XSB]
Solids (by weight)	50%
pH	7.5
Tg	-50° C
Solvent or Water Based	Water
Emulsifier	Anionic
Physical Form	Liquid
Bulk Density	8.3 lb/gal
Brookfield Viscosity	< 250 cps (LVT #2 @ 60 rpm, 25° C)
Specific Gravity	1.00
Surface Tension	50 dyn/cm
Residue	<150 ppm
Foaming Tendency	Low
Odor	Low
UV Stability	Excellent
Mechanical Stability	Excellent

Key Advantages

- Solvent-free and water-based for easy clean up
- Easily diluted with water
- Forms a tacky adhesive bond for the first layer of rubber
- Minimizes clogging of application equipment





Application Information

- Base Layer Preparation: Pave at least 2" of asphalt over the existing area or on top of a foundation. The asphalt should be allowed to cure and off-gas for 14 days prior to track construction.
- Do not install during rain. The latex may be washed away. Do not install if temperatures drop below 50° F. The latex performance may be compromised.

Storage & Handling Guidelines

Available Packaging	Totes (IBC) - 2204lbs approx. 265 gallons
Handling	<ul style="list-style-type: none">• See Safety Data Sheet (SDS) for additional information.• Stir and mix well before use.
Recommended Storage Solutions	<ul style="list-style-type: none">• Keep container tightly covered when not in use.• Do not expose product or container to direct sunlight or freezing temperatures.• Avoid prolonged storage at high temperatures.• Store in original packaging.
Recommended Storage Temperature	22° C (70° F)
Freeze / Thaw Stability	This product is not freeze-thaw stable.
Shelf Life	6 months (when stored as recommended)

AcryTech

2660 Easterly Place
Decatur, GA 30035
880-294-0428
www.tennispaint.com